

PATHFINDER II™

***Accurate, Economical
Cable Locator***



- ***Lightweight, Compact, Easy to Use***
- ***Works Near Power Lines***
- ***Optimal Path and Depth Locating***

Pathfinder II packs high performance in a small, easy to use size, at an affordable price.



PATHFINDER II™

Pathfinder II packs high performance in a small, easy to use size, at an affordable price.



FEATURES:

- **Performance**
 - Extremely sensitive receiver picks up signals easily.
 - Optimal path and depth locating accuracy.
- **Convenience:**
 - Lightweight, compact, hand-held portable locator is easy to operate, yet designed for years of rugged use.
- **Price:**
 - The price is right. In fact, we challenge you to find a better utility locator anywhere at this price.
- **Superior Technology:**
 - Locates near power lines without interference.
- **Variable Pitch Audio:**
 - Allows easier identification of cable path.



SPECIFICATIONS:

RECEIVER

Input Frequency:	82Hz; 815Hz
Noise Rejection:	116 dB Minimum
Gain Control:	126 dB Minimum
Meter Output:	Analog, Null Type
Speaker Output:	Variable pitch tone, 1-4.2kHz
Power Source:	8 AA-type Alkaline Batteries
Battery Life:	100 Hours
Operating Temperature:	-4° to +133°F (-20° to +55°C)
Size:	13" x 3" x 3" (33cm x 7.6cm x 7.6cm)
Weight:	1.7lb. (.62kg)

TRANSMITTER

Tone Frequency:	82Hz; 815Hz
Hook-up Method:	Direct Connection; Inductive Coupling from Transmitter Case; Inductive Coupling with Flexicoupler
Output Power:	1 Watt Nominal, Autoloading
Maximum Open Circuit Voltage:	30V Peak AC
Operating Temperature:	-4° to +133°F (-20° to +55°C)
Power Source:	8 C-type Alkaline Batteries
Battery Life:	120 Hours
Weight:	6.2lb. (2,8kg)
Size:	Carry Case with Receiver Storage Compartment: 16" x 6.3" x 5" (40.6cm x 16cm x 13cm)